(19) World Intellectual Property Organization

International Bureau



I CONS RUNIDO A BEREN KAN BANK BANK BANK AKA 18 KU BANK KAN KAN KAN KAN KAN BANKAN KAN KAN KAN KAN KAN KAN KAN

(43) International Publication Date 10 February 2005 (10.02.2005)

PCT

(10) International Publication Number WO 2005/012947 A1

(51) International Patent Classification7: 3/06, H01Q 1/04

G01V 3/15,

(21) International Application Number:

PCT/GB2004/003267

(22) International Filing Date:

28 July 2004 (28.07.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0317649.2

28 July 2003 (28.07.2003)


(71) Applicant (for all designated States except US): ELEC-TROMAGNETIC GEOSERVICES AS [NO/NO]; Stiklestadveien 1, N-7041 Trondheim (NO).

(71) Applicant (for 1S only): REES, David, Christopher

(74) Agents: REES, David, Christopher et al.; Kilburn & Strode, 20 Red Lion Street, London WC1R 4PJ (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).



the dipole antenna comprising a first electrode (18) mounted on a cable (19) and located near to the current source and a second electrode (21) mounted on a cable (22) and located further away from the current source, each electrode being electrically connected to the current source. The transmitter antenna may be deployed by being towed behind a vessel (14).